

# Ka-66

**iNetVu®**  
by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS

The iNetVu® Ka-66 Drive-Away Antenna is a 66 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for direct broadband access over any configured satellite. The system works seamlessly with the iNetVu® 9000 Controller providing fast satellite acquisition within minutes, anytime anywhere.



### Features

- One-Piece high surface accuracy, dual optics, offset feed, steel reflector
- Integrated with Telesat / Wildblue Transceiver
- Designed to work with the iNetVu® controller
- Works seamlessly with Linkstar Ka modem
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires any Ka satellite within 2 minutes
- Locates satellites using the most advanced satellite acquisition methods
- Based on Skyware (Raven) 66 cm antenna
- Standard 2 year warranty

### Application Versatility

If you operate Ka-band in North America, the Ka-66 system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.

**C-COM**  
SATELLITE SYSTEMS INC.

[www.c-comsat.com](http://www.c-comsat.com)  
613-745-4110 | 877-463-8886

Specifications are subject to change

September 2012

# Ka-66



## TECHNICAL SPECIFICATIONS

### Mechanical

Reflector	66cm Elliptical Antenna, Dual Offset
Mount Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass $\pm 2^\circ$ Tilt sensor $\pm 0.2^\circ$
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0 - 60°
Elevation Deploy Speed	Variable 2°/sec typ.
Azimuth Deploy Speed	Variable 15°/sec Max., 10°/sec typ.
Peaking Speed	0.2°/sec

### Environmental

Survival	
Wind Deployed	200 km/h (124 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	75 km/h (47 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)

### Electrical

Rx & Tx Cables	2 RG6 cables - 9.1m (30 ft) each	
Control Cables		
Standard	9.1m (30 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	<b>Receive</b>	<b>Transmit</b>
Frequency (GHz)	19.70 - 20.20	29.50 - 30.00
Feed Interface (Circular)	RG6	RG6
Midband Gain Co-Pol ( $\pm 0.2$ dB)	40.40 @19.95 GHz	44.40 @29.75 GHz
Antenna Noise Temp. (K)	30° EL= 44° typical	
Sidelobe Envelope, Co-Pol (dBi)		
1.6° < $\theta$ < 7°	29 - 25 Log $\theta$	
7° < $\theta$ < 9.2°	+8	
9.2° < $\theta$ < 48°	32-35 Log $\theta$	
48° < $\theta$ < 180°	-10 (typical)	
Cross-Polarization (on axis)	> 35 dB	> 35 dB
VSWR	1.3:1	

### RF Interface

Radio Mounting	Feed Arm
Coaxial	RG6U from Transceiver to Base Connector

### Physical

Mounting Plate	L: 132 cm	(52")
Stowed Dish Ext. Dims	W: 56 cm	(22")
	L: 135 cm	(53")
	W: 76 cm	(30")
	H: 47 cm	(18.5")
Deployed Height	109 cm	(43") Max.
Weight	50 kg	(110 lbs)

### Motors

Electrical Interface	12VDC	15 Amp (Max.)
----------------------	-------	---------------

### Shipping Weight & Dimensions

Crate: 155 cm x 122 cm x 54 cm (61" x 48" x 21"), 106 kg (233 lbs)